

VN-V26U IP Network True Day / Night with Audio

Progressive Scan CCD with Dual Streaming, Colour / Mono IR Sensitive.



Description

Main features

Additional features

Technical specs

Brochures and manuals

See all in one page



Description

Versatile True Day / Night Security Camera with Bi-Directional Audio, and Dual Streaming, MPEG-4 / Motion JPEG.

Main features

- 1/4" Progressive scan CCD
- Full-frame dual stream
- Day / Night function (IR cut filter)
- Bi-Directional Audio support

Additional features

- Easy Wide-D function
- PoE / 24V AC Power supply

- Compatible with VR-N900U / 1600E

Technical specs

Image device:

1/4" Progressive scan CCD, 330,000 pixels

Minimum required Illumination:

Colour mode:0.3 lx (Video 25%, F1.2, AGC on) 0.6 lx (Video 50%, F1.2, AGC on) B&W mode:0.03 lx (Video 25%, F1.2, AGC on) 0.06 lx (Video 50%, F1.2, AGC on)

White balance:

ATW (Auto), AWC

Automatic electronic shutter:

1/30 to 1/100000 (10 steps)

AGC:

OFF/ MID/ HIGH/ SUPER

Sense Up

OFF / x2, 4, 8, 16, 32, 62

Back Light Compensation:

On (4 types) / Off

Gamma level

Adjustable

Day / Night

IR cut filter ON / OFF

Private Mask

Free shape, Unlimited number of masked area

Internal storage capacity

8 MB SDRAM

Display Mode

Custom / LCD1 / LCD2 / CRT

Monitor output

RCA, NTSC / PAL selectable (For installation only, unavailable network output simultaneously)

Internal microphone

Omnidirectional Output sensitivity: 43 db (0db=1V/Pa) Standard input level:85db

Audio output:

Line out x 1 (200 ohms Maximum 2.2Vp-p) Mini jack dia. 3.5 mono

Lens mount:

C / CS

Network Connectivity:

RJ45 (cat5) 10Base-T, 100Base-TX (Auto negotiation, Manual)

Picture Resolution (pixel)

640 x 480, 320 x 240 (pixels)

Picture compression

JPEG, MPEG-4

Compression format

JPEG: variable file size (VFS) / Average file size (AFS) selectable. MPEG-4: bit Rate adjustable.

Compression level

JPEG: VFS 7 steps, AFS 10kb to 100kb. MPEG-4 : Bit rate adjustable

Frame Rate (max)

Max 30 fps (640 x 480, Dual stream)

Audio compression format

u-law 64 kbps AD/DA 16 bits Fs=8kHz, mono

Data transmission

Unicast / Multicast (IGMP Ver 2)

Viewer

Web browser (IE6.0)
Dual stream function
Yes (Mac 30fps)
Max.clients
20
Other function
Motion detection, Mail notice function, Web server function, FTP client function, DHCP client function, SNTP client function, Access protection (3 level password)
System requirements:
PC: Windows XP Pro(SP2) / Home (SP2), IE6.0, Pentium 4 (1.5GHz), 1GB memory Display and video card: 1024 x 768 True colour (24 bit or 32 bit) VRAM 256MB
Power requirement:
24V AC (50Hz/ 60Hz) / 48V DC (PoE)
Power consumption:
24 V AC 0.35A / PoE 115mA (5.5W)
Operating Temperature:
-10 to 50 deg.C / 14 to 122 deg.F (0 to 40 deg.C / 32 to 104 deg.F recommended)
Dimensions (WxHxD):
66 x 63 x 126 mm
Weight:
530g

Accessories

Brochures and manuals



[Brochure information](#)



[Instruction manual \(from the JVC Professional Europe Service Information System\)](#)

Links

Miscellaneous