

LM-H191EB LCD 19" Monitor

LCD 19" Monitor



Description

Main features

Additional features

Technical specs

Accessories

Brochures and manuals

See all in one page



Description

19-inch LCD monitor designed specifically for the professional security and surveillance market. Built to the highest specifications, it combines superb visual performance and precise high resolution images.

Main features

- Fire-retardant front cabinet and metal rear cabinet
- Non-glare panel for 24/7 viewing
- Tilt positions are easily adjusted for operator viewing, with easy to operate front panel controls
- Built-in power supply and the option of a rack mount adaptor (RK-C179L2EA)
- Accepts Video BNC, VGA and DVI input signals for use with analogue and digital network recording equipment

Additional features

When operating the four picture modes (standard, dark enhanced, vivid and dynamic), the LM-H191 allows users and installers to select their screen image to a desired performance and ensuring the best quality captured image during the day or night.

Technical specs

Description:

19-inch LCD monitor, combining superb visual performance and precise high resolution images. Rugged and reliable it is intended for 24/7 use in the most challenging environments.

Colour system:

PAL and NTSC

LCD Panel:

19" active matrix TFT

Screen Size:

Width: 376mm, Height 301mm

Pixel Count:

1280 x 1024 (SXGA)

Display Colours:

16.77 million

Scanning:

H: 31.5 kHz - 65 kHz V:56 Hz - 75 Hz

Some signals within this frequency range may not be displayed, depending on the computer ("Out of range" appears).

Viewing Angle:

178 degrees horizontal, 178 degrees vertical

Brightness:

300 cd/m²

Contrast Ratio:

1300:1

Response Time:

8 msec

Input/Output:

Support Format Video: pComposite video: NTSC, PAL, Monochrome (50 Hz/60 Hz)

PC: DVI - D, Analog RGB (D-sub 15-pin)/VGA: 640 x 480 (60 Hz)*, 640 x 576 (50 Hz)/SVGA: 800 x 600* (56 Hz)*, 800 x 600 (60 Hz)/ XGA: 1024 x 768 (60 Hz), 1024 x 768* (70 Hz)*/WXGA: 1280 x 768 (60 Hz)/SXGA: 1280 x 1024 (60 Hz)/ US TEXT: 720 x 400* (70 Hz)

Remote control:

Make/Trigger (RJ45)

Audio output:

internal Speaker: 0.8 W (monaural)

Power requirement:

AC 120/220 - 240 V, 50 Hz/60 Hz

Dimensions:

w/o stand: 413x364x74mm
with stand: 413x405x199mm

Accessories

- [RK-C179L2EA](#)
- 19" Rack Mount

Brochures and manuals



[PDF Brochure LM-H191](#)



[RK-C157L1G - All languages](#)



[Instruction manual \(from the JVC Professional Europe Service Information System\)](#)

Links

Miscellaneous