

## VN-V225U Network IP Internal Mini Dome Camera

3.8x 2.8-10.5mm Varifocal Lens Dual Streaming VGA MJPEG/MPEG-4



### [Description](#)

### [Main features](#)

### [Technical specs](#)

### [Brochures and manuals](#)

### [See all in one page](#)



### **Description**

VN-V225U fixed network dome camera with reliable Day & Night surveillance and JVC's patent pending new Fine Focus Adjust mechanism.

### **Main features**

- 1/4 Progressive Scan CCD + Built-in 3.8x variable-focal
- Motion JPEG and MPEG-4 Full Frame Dual Stream
- VGA MJPEG and MPEG-4 at 30fps each simultaneously
- True Day/Night for night time surveillance
- Bi-Directional Audio Support
- Two-way audio communication via mic-in and line-out
- Free Shape Privacy Masking
- Compact enclosure dia. 145mm, 5-3/4 inch

- New Fine Focus Adjust mechanism [Patent pending]
- PoE / 24 VAC power supply
- Great partners about to support Milestone, Verint, AMX
- Supported by JVC VR-N900/1600 and VN-RS800U system

## Additional features

## Technical specs

Compression:

Motion Jpeg / Mpeg-4 Dual Stream (30fps simultaneous streams)

Day / Night

True Day / Night (Mech IR cut Filter)

AUDIO:

Bi-Directional

Lens:

3.8x 2.8-10.5mm

Power requirement:

PoE / 24 Vac

Other:

Free shape masking

## Accessories

## Brochures and manuals

- 

[VN-V225U Information](#)

- 

[Instruction manual \(from the JVC Professional Europe Service Information System\)](#)

## Links

## Miscellaneous